


# Hercules

## 6 Simple Steps to Wash, Wax & Seal In Only 5 Minutes!




**#1** Vehicle is pulled under rectangular frame. Operator activates pneumatic systems by pressing wash button. Frame rinses vehicle in 8 seconds with 52 brass water jets on the down stroke.



**#2** Frame stops at hubcap level. Chemical pumps are activated. Frame rises, spraying water and environmentally safe biodegradable chemical over entire vehicle in 8 seconds.



**#3** According to the size of the vehicle, 2, 3, or 4 minutes elapsed time is provided by a high tech electronic computer. This time allows the operator to use the applicator to break the static bond. Dirt is easily washed away on rinse cycle.



**#4** High pressure air-water gun is used to remove disc brake film, ice, snow and caked on mud under wheel arches, undercarriage as well as degreasing the engine compartment.



**#5** Bell signals end of detailing cycle. Frame automatically lowers and rises, rinsing the vehicle in under 16 seconds.



**#6** Frame completes the final cycle applying Protective hi-glo paint sealant to vehicle - Producing high shine. Where applicable, optional spot-free rinse sprays deionized water eliminating chamois or towel drying for a "showroom shine".

**TOTAL TIME FOR A WASH-WAX AND SEAL -  
WITH A SPOT FREE RINSE ... 5 MINUTES!**