

Reverse Osmosis

STANDARD FEATURES PROVIDE MANY BENEFITS



- Up to 1600 gallons a day
- State-of-the-art, This Film Composite, spiral wound reverse osmosis elements provide high rejection of dissolved minerals, bacteria, pyrogens, colloids, particles, organics, and silica.
- PVC and Noryl plastic module housings are corrosion resistant. Connections between housing are internal to obtain maximum performance from the elements.
- Jet Pressure Pump provides optimum energy efficiency and quiet operation.
- Hinged Stainless Steel control enclosure and accessible major components provide maximum serviceability and space efficiency.
- Cartridge prefiltration system with replaceable element removes suspended particles to extend component life.
- Front mounted pressure indicators and regulator allow easy monitoring and controlling of pumping conditions.
- Low Pressure switch, for pump protection.

SYSTEM SPECIFICATIONS

Feed Water Pressure (flowing):	20-75 psig
Feed Water Temperature:	33-100°F
Power Requirements:	115VAC/60Hz/1Phase
Water Connections:	Feed - 1/2" NPTE Product - 3/8" Tube Concentrate - 3/8" Tube
Installation Dimensions:	Height - 65" Width - 18" Depth - 18"

NOTE: Operational, maintenance and replacement requirements are essential for this product to perform as advertised.



Hercules

Polishes Your Image

95 West Hills Rd. • Huntington Station, NY 11746 • Tel 631-423-6900 Fax 631-385-3222
USA & CANADA (800) 227-0495 • www.herculescarwash.com